

Butterfly Valve

Ordering Information

- When ordering, specify material, gauge (if non-standard), dimension and end styles.
- A standard locking quadrant handle enables users to regulate air volumes in clean air applications.
- For clean air applications only.



| Ø in. | Length in. | Std Weight Lbs |
|-------|------------|----------------|
| 3 | 8 | 1.50 |
| 4 | 8 | 1.65 |
| 5 | 8 | 2.00 |
| 6 | 8 | 2.40 |
| 7 | 8 | 3.20 |
| 8 | 13 | 4.10 |
| 9 | 13 | 4.85 |
| 10 | 13 | 5.45 |
| 11 | 13 | 7.00 |
| 12 | 13 | 8.40 |
| 13 | 17 | 9.75 |
| 14 | 17 | 11.85 |
| 15 | 17 | 12.70 |
| 16 | 17 | 14.20 |
| 17 | 23 | 16.10 |
| 18 | 23 | 18.00 |
| 19 | 23 | 22.50 |
| 20 | 23 | 27.75 |
| 21 | 23 | 30.00 |
| 22 | 23 | 32.40 |
| 23 | 23 | 37.50 |
| 24 | 23 | 37.90 |

QF / Flanged Material Options

| | | Galv | | | SS | | |
|----------|----|-----------|--------|----------|-----------|--------|----|
| | | Size (in) | | | Size (in) | | |
| Gauges | | Min. Ø | Max. Ø | Gauges | Min. Ø | Max. Ø | |
| Standard | 22 | 3 | 12 | Standard | 22 | 3 | 12 |
| | 20 | 13 | 24 | | 20 | 13 | 24 |
| Optional | 18 | 4 | 24 | Optional | 18 | 4 | 24 |
| | 16 | 8 | 24 | | 16 | 8 | 24 |

| Additional Product Components and Notes | | |
|---|----------------------|---------------------------|
| Quadrant (3/8" dial regulator) | Butterfly Valve Size | Mfr. Part No. (Duro Dyne) |
| | 3" - 11" galvanized | KSR195L |
| | 12" - 24" galvanized | KS385 |
| | All SS | KR3SS |



Temperature Rating: Max. temperature limited to 225°F due to the properties of the grommet (Styrene Butadiene Rubber, durometer hardness 60).

