


Viewing Spool

Ordering Information

- When ordering, specify material, gauge (if non-standard), dimension and end styles.

- Air flow directional arrow sticker is attached to product.
- Section of acrylic glass with QF ends allowing user to view material flow through ductwork.



Ø in.	Length in.	Std Weight Lbs
3	12.5	2.50
4		3.00
5		3.50
6		4.10
7		4.60
8		5.00
9		5.45
10		6.25
11		7.10
12		8.20
13		11.25
14		14.10
15		18.25
16		22.60
18		18.00

QF / Flanged Material Options

Galv				SS			
Gauges		Size (in)		Gauges		Size (in)	
		Min. Ø	Max. Ø			Min. Ø	Max. Ø
Standard	22	3	12	Standard	22	3	12
	20	14	18		20	14	18
Optional	18	4	18	Optional	18	4	18
	16	6	18		16	6	18

Construction

Seam: longitudinal seam is laser welded.

Collars: Collars have a laser welded longitudinal seam.

Acrylic: Acrylite® - clear, .250 thick

Optional End Styles: Standard QF end can be changed to Raw ID (RI), Raw OD (RO), No Fitting (NF), Hose Adapter (RAWFLEX), Flat Flange (FFL), Angle Flange (AFL), or Van Stone (VS).



Temperature Rating: Max. temperature limited to 225°F due to properties of the acrylic viewing port.