

# QF Floor Sweep

Ø mm	Collar Rolled Edge (nom. mm.)	X mm	Length mm	Y mm	Weight kg	Galvanised Steel
80	6	305	408	155	0,6	0,7
100	6				1,0	
125	6				2,0	
140	6				2,9	
150	6				3,4	
160	6				3,8	
180	8				4,9	
200	8				5,9	
224	8				6,9	
250	8				8,3	
300	10	10,7				

Temperature Rating of Product Components		
° C	Floor Sweep	Sealants
200°	Galvanised Steel	Joka Seal Metal Sealant 2315
121°		
-20°		

Additional Notes
At temperatures ranging between 200° C and 250° C, the zinc-iron alloy layers in galvanised steel will continue to provide a high level of protection from corrosion. However, there may be some peeling, changes in mechanical properties, and reduction in the corrosion protection. Recommended max. service temperature is 200° C.

Compliance / Rating of Product Components		
Product	Material	Compliance / Rating
Floor Sweep	Galvanised	DX51D with Z275 Coating
Joka Seal Metal Sealant 2315	Acetone blend	AAMA Specification 801.1

**Construction**

**Body:** lapped, spot welded and caulked.

**Collars:** have a laser welded longitudinal seam. Collars are attached to the body using a raised hemmed, spot welded seamed construction and are caulked.

**Ends**

Standard QF end can be changed to Raw ID (I/D), Raw OD (O/D), Hose Adapter (FX), Flat Bar Flange (FL), or 6mm turned out edge (FB).

